

Appl. No.: 09/851,340  
Amdt. dated March 2, 2004  
Reply to Office Action of January 2, 2004

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A method of displaying frames of images using a wearable display device, comprising:
- generating an inner region display signal of the frame of an image;
  - determining at least one of a motion, brightness or color characteristic from the inner region display signal;
  - generating an outer region display signal of the frame of the image using the at least one motion, brightness or color characteristic;
  - displaying an inner region of ~~an~~ the frame of the image on a display using the inner region display signal; and
  - displaying an outer region of the frame of the image on the display using the outer region display signal, wherein the outer region is of substantially lower resolution than the inner region.
2. (Currently Amended) The method of claim 1, wherein ~~the step of~~ generating an outer region display signal further comprises:
- adjusting the outer region display signal so that the outer region of the frame of the image blends with the inner region of the frame of the image.
3. (Currently Amended) The method of claim 1, wherein ~~the step of~~ displaying an outer region of the frame of the an image further comprises:
- displaying an outer region of less than 5 cycles per degree resolution.

al  
cmt

**Appl. No.: 09/851,340**  
**Amdt. dated March 2, 2004**  
**Reply to Office Action of January 2, 2004**

4. (Currently Amended) The method of claim 3, wherein ~~the step of~~ displaying an inner region of ~~an~~ the frame of the image further comprises:  
displaying a center of the inner region of at least 15 cycle per degree resolution.
5. (Currently Amended) The method of claim 3, wherein ~~the step of~~ displaying an outer region of ~~an~~ the frame of the image further comprises:  
illuminating an array of red, blue and green lights.
6. (Currently Amended) The method of claim 3, wherein ~~the step of~~ displaying an outer region of ~~an~~ the frame of the image further comprises:  
illuminating an array of white lights.
7. (Currently Amended) The method of claim 1, wherein ~~the step of~~ displaying an outer region of ~~an~~ the frame of the image further comprises:  
shining red, blue and green lights into a user's field of view.
8. (Currently Amended) A wearable display, comprising:  
a display ~~having comprising~~ a plurality of pixels, the display having an  
inner region and an outer region of substantially lower resolution  
than the inner region; and  
a controller operably coupled to the display, wherein the controller  
generates an inner region display signal, and an outer region  
display signal using at least of one of a motion, brightness or color  
characteristic from the inner region display signal.
9. (Original) The display of claim 8, wherein the outer region is of less than 5  
cycles per degree resolution.
10. (Original) The display of claim 8, wherein the inner region is of at least 15  
cycle per degree resolution at a center of the inner region.

**Appl. No.: 09/851,340**  
**Amdt. dated March 2, 2004**  
**Reply to Office Action of January 2, 2004**

11. (Original) The display of claim 9, wherein the outer region comprises:  
an array of red, blue and green lights.
12. (Original) The display of claim 9, wherein the outer region comprises:  
an array of white lights.
13. (Currently Amended) A method of displaying images using a wearable display, comprising:  
determining an amount of distortion for image signal data, the distortion acting to distort a source image conveyed by the image signal data so that a field of view of the source image is expanded;  
adjusting the image signal data so that the source image conveyed by the image signal data is distorted according to the determined amount of distortion;  
generating a display signal using the adjusted image signal data; and  
displaying an a distorted image on a display by using the display signal.
14. (Original) The method of claim 13, wherein the step of adjusting the image signal data comprises:  
creating a distortion ratio between an inner region and an edge of the source image of between 2:1 and 20:1.
15. (Original) The method of claim 14, comprising:  
sampling a source image signal to obtain the image signal data.
16. (Currently Amended) A wearable display, comprising:  
a display comprising a plurality of pixels, the display having an inner region and an outer region; and  
a controller operably coupled to the display, wherein the controller obtains image signal data from a source image signal and generates a display signal by determining an amount of distortion for the image signal data, and adjusting the

al  
cmt

Appl. No.: 09/851,340  
Amdt. dated March 2, 2004  
Reply to Office Action of January 2, 2004

image signal data so that a source image conveyed by the image signal data is distorted according to the determined amount of distortion, ~~the distortion-distorting the source image distorted on the display in the outer regionso that a field of view of the image is expanded to the outer region of the display.~~

17. (Original) The display of claim 16, wherein the distortion ratio between an inner region and an edge of the source image is between 2:1 and 20:1.

al  
cmd  
18. (Original) The wearable display of claim 16, comprising:  
an image source coupled to the controller, wherein the image source generates the source image signal.

19. (Original) The wearable display of claim 18, wherein the controller comprises:  
a processor operably coupled to the image source, wherein the processor samples the source image signal.

20. (Original) A wearable display, comprising:  
a display for displaying images;  
a controller operably coupled to the display, wherein the controller obtains image signal data from a source image signal and generates a display signal for display by the display; and  
optics arranged in the wearable display, wherein the optics modify an image displayed by the display by distorting an outer region of the image by a greater amount than an inner region of the image so that a field of view of the image is increased.

21. (Original) The wearable display of claim 20, wherein a distortion ratio between a portion of the outer region and a portion of the inner region is between 2:1 and 20:1.